

PERFORMANCES HYDRAULIQUES-TIC-TTI

| ENROULEUR : STRUCTURE 2061 DIAMETRE : \varnothing 125 LONGUEUR : 600 M | | | | | | | REEL MACHINE : STRUCTURE 2061 DIAMETER : \varnothing 125 LENGTH : 600 M | | | | | |
|--|-------|----------------------------|--------|----------|---------|---------|---|-------------|-------------|------------------------|-------------|-------------|
| ENROULEUR REEL MACHINE | | CANON SR 150 GUN SR 150 | | | | | | | | | | |
| pression | débit | p. canon | buse | portée | esp. | surface | DOSE EN mm | | | / DOSE IN mm | | |
| pressure | flow | p. gun | nozzle | distance | spacing | area | VITESSE EN m/h | | | / WINDING SPEED IN m/h | | |
| bar | m3/h | bar | mm | m | m | has | 15 | 20 | 30 | 40 | 50 | 60 |
| 6.1 /6.6 | 40.4 | 4 | 24 | 45.5 | 72 | 4.6 | 37 | 28 | 19 | 14 | | |
| 6.8 /7.3 | 42.9 | 4.5 | 24 | 47.5 | 72 | 4.6 | 40 | 30 | 20 | 15 | | |
| 7.5 /7.9 | 45.2 | 5 | 24 | 49 | 78 | 5.0 | 39 | 29 | 19 | 14 | 12 | |
| 8.1 /8.6 | 47.4 | 5.5 | 24 | 50.5 | 78 | 5.0 | 41 | 30 | 20 | 15 | 12 | 10 |
| 7.4 /7.9 | 51.1 | 4.5 | 26 | 49.5 | 78 | 5.0 | 44 | 33 | 22 | 16 | 13 | 11 |
| 8.1 /8.6 | 53.9 | 5 | 26 | 51.5 | 78 | 5.0 | 46 | 35 | 23 | 17 | 14 | 12 |
| 8.8 /9.3 | 56.6 | 5.5 | 26 | 53 | 84 | 5.4 | 45 | 34 | 22 | 17 | 13 | 11 |
| 8.2 /8.7 | 61 | 4.5 | 28 | 52.5 | 84 | 5.4 | 48 | 36 | 24 | 18 | 15 | 12 |
| 9.0 /9.5 | 64.4 | 5 | 28 | 54 | 84 | 5.4 | 51 | 38 | 26 | 19 | 15 | 13 |
| 9.8 /10.3 | 67.6 | 5.5 | 28 | 55.5 | 84 | 5.4 | 54 | 40 | 27 | 20 | 16 | 13 |
| 9.2 /9.8 | 71.9 | 4.5 | 30 | 55 | 84 | 5.4 | 57 | 43 | 29 | 21 | 17 | 14 |
| 10.1 /10.7 | 75.8 | 5 | 30 | 56.5 | 90 | 5.8 | 56 | 42 | 28 | 21 | 17 | 14 |
| TEMPS D'ENROULEMENT COMPLET EN HEURE TIME FOR COMPLETE WINDING IN HOUR | | | | | | | 40.0 | 30.0 | 20.0 | 15.0 | 12.0 | 10.0 |