

## PERFORMANCES HYDRAULIQUES TIC-TTS

ENROULEUR : OPTIMA 1005 DIAMETRE : $\varnothing$ 82 LONGUEUR : 260 M								REEL MACHINE : OPTIMA 1005 DIAMETER : $\varnothing$ 82 LENGTH : 260 M					
Turbine	ENROULEUR REEL MACHINE		CANON SR 100 GUN SR 100					DOSE EN mm			DOSE IN mm		
Buse	pression	débit	p. canon	buse	portée	esp.	surface	VITESSE EN m/h			WINDING SPEED IN m/h		
Nozzle	pressure	flow	p. gun	nozzle	distance	spacing	area	10	20	30	40	50	60
mm	bar	m3/h	bar	mm	m	m	has						
16	5.2 /6.2	17.4	3.5	16	34.5	54	1.6	32	16	11	8	6	5
16	5.7 /6.8	18.7	4	16	36	54	1.6	35	17	12	9	7	6
16	6.3 /7.4	19.7	4.5	16	37.5	60	1.7	33	16	11	8	7	5
18	6.9 /8.0	20.8	5	16	38.5	60	1.7	35	17	12	9	7	6
18	7.4 /8.5	21.8	5.5	16	39.5	60	1.7	36	18	12	9	7	6
18	5.5 /6.6	22.4	3.5	18	37	54	1.6	41	21	14	10	8	7
18	6.1 /7.2	23.9	4	18	38.5	60	1.7	40	20	13	10	8	7
18	6.7 /7.8	25.3	4.5	18	40	60	1.8	42	21	14	11	8	7
18	7.3 /8.4	26.6	5	18	41.5	66	1.9	40	20	13	10	8	7
18	6.0 /7.1	28.4	3.5	20	39.5	60	1.7	47	24	16	12	9	8
18	6.7 /7.8	30.4	4	20	41.5	66	1.9	46	23	15	12	9	8
18	7.4 /8.5	32.6	4.5	20	43	66	1.9	49	25	16	12	10	8
18	8.0 /9.1	34.1	5	20	44	66	1.9	52	26	17	13	10	9
18	8.7 /9.8	35.7	5.5	20	45.5	72	2.1	50	25	17	12	10	8
18	7.4 /8.5	37.6	4	22	43.5	66	1.9	57	28	19	14	11	9
18	8.2 /9.2	39.9	4.5	22	45	72	2.1	55	28	18	14	11	9
18	8.9 /10.0	42	5	22	46.5	72	2.1	58	29	19	15	12	10
18	8.4 /9.5	45.8	4	24	46	72	2.1	64	32	21	16	13	11
TEMPS D'ENROULEMENT COMPLET EN HEURE TIME FOR COMPLETE WINDING IN HOUR								<b>26.0</b>	<b>13.0</b>	<b>8.7</b>	<b>6.5</b>	<b>5.2</b>	<b>4.3</b>